Safety Data Sheet
OPTIBOND XTR PRIMER

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : OPTIBOND XTR PRIMER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use

Function or use category : Dental materials.

Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier
Kerr Italia S.r.l.
Via Passanti, 332
84018 Scafati (SA) - Italy
T +39-081-850-8311
E-mail: safety@kerrhawe.com

Manufacturer
Kerr Corporation
1717 West Collins Avenue
92867 Orange – CALIFORNIA (U.S.A.)
T 00-800-41-050-505
safety@kerrhawe.com

Contact person : safety@kerrhawe.com - tel. 00-800-41-050-505 (08.00-17.00)

1.4. Emergency telephone number

Emergency number : CHEMTREC® Emergency Call Center. Emergency Telephone Number (for USA only) 001-800-424-9300 International and Maritime Telephone Number +1 (703) 527-3887

Country	Organisation/Company	Address	Emergency number
United Kingdom	National Poisons Information Service (Newcastle Unit)	Claremont Place Newcastle-upon-Tyne, Newcastle	+44 191 2606182/+44 191 2606180 24H

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H336

Full text of classification categories and H statements : see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02 GHS07

Signal word (CLP) : Danger

Hazardous ingredients : 2-hydroxyethyl methacrylate, acetone, propan-2-one, propanone

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P261 - Avoid breathing spray, vapours, gas, mist
P264 - Wash hands, forearms and face thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear eye protection, protective gloves
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor/physician if you feel unwell
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use sand, foam, extinguishing powder, carbon dioxide (CO2) for extinction
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P501 - Dispose of contents/container to ...

Extra phrases : The product is seen as a medical device and therefore not subject to labelling (EU-regulation 1907/2006, article 2, paragraph 6c).

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-hydroxyethyl methacrylate	(CAS No) 868-77-9 (EC no) 212-782-2 (EC index no) 607-124-00-X (REACH-no) 01-2119490169-29	=>10-<50	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317
acetone, propan-2-one, propanone	(CAS No) 67-64-1 (EC no) 200-662-2 (EC index no) 606-001-00-8 (REACH-no) 01-2119471330-49	=>20-<35	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
ethanol, ethyl alcohol	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5 (REACH-no) 01-2119457610-43	=>4-<15	Flam. Liq. 2, H225

Full text of H-statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

First-aid measures general : No particular/specific measures required.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : In all cases of doubt, or when symptoms persist, seek medical attention.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No specific measures identified.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire. Foam, carbon dioxide (CO2) and powder.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : Product is not explosive.

Hazardous decomposition products in case of fire : Carbon monoxide. Carbon dioxide.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear appropriate personal protective equipment - see Section 8. Avoid contact with skin and eyes. Remove ignition sources. No open flames. No smoking. Use special care to avoid static electric charges. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas.

For non-emergency personnel

No additional information available

For emergency responders

No additional information available

6.2. Environmental precautions

Discharging into rivers and drains is forbidden.

6.3. Methods and material for containment and cleaning up

For containment : Collect all waste in suitable and labelled containers and dispose according to local legislation.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Precautions for safe handling : Keep container tightly closed. Avoid contact with skin and eyes. Ensure good ventilation of the work station. Prevent the build-up of electrostatic charge. Use only non-sparking tools. No open flames. No smoking. Keep away from sources of ignition - No smoking.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry protected location to prevent any moisture contact. Keep container tightly closed. Keep cool. Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Store in a well-ventilated place.

Incompatible materials : Oxidizing substances.

7.3. Specific end use(s)

Consult the supplier for further information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

ethanol, ethyl alcohol (64-17-5)		
United Kingdom	Local name	Ethanol
United Kingdom	WEL TWA (mg/m³)	1920 mg/m³
United Kingdom	WEL TWA (ppm)	1000 ppm
acetone, propan-2-one, propanone (67-64-1)		
EU	Local name	Acetone
EU	IOELV TWA (mg/m³)	1210 mg/m³
EU	IOELV TWA (ppm)	500 ppm
United Kingdom	Local name	Acetone
United Kingdom	WEL TWA (mg/m³)	1210 mg/m³
United Kingdom	WEL TWA (ppm)	500 ppm
United Kingdom	WEL STEL (mg/m³)	3620 mg/m³
United Kingdom	WEL STEL (ppm)	1500 ppm

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses.

Hand protection : Butylrubber protective gloves. Neoprene. Layer thickness : 0,2 - 0,4 mm. Breakthrough time : 6 (> 480 minutes). STANDARD EN 374.

Eye protection : Safety glasses. STANDARD EN 166.

Skin and body protection : Wear suitable protective clothing

Respiratory protection : No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation



Other information : Do not eat, drink or smoke during use. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Paste.

Colour : Pale yellow.

Odour : Fruity.

Odour threshold : No data available

pH : > 2

Relative evaporation rate (butylacetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : 13 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

Vapour pressure : No data available

Relative vapour density at 20 °C : No data available

Relative density : 1

Solubility : In water, material is partially soluble.

Log Pow : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : Product is not explosive.

Oxidising properties : Flammable liquid and vapour.

Explosive limits : No data available

9.2. Other information

Additional information : None to our knowledge

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No polymerization.

10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition. Keep away from heat and direct sunlight.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

No decomposition if stored normally.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity : Not classified

2-hydroxyethyl methacrylate (868-77-9)	
LD50 oral rat	5050 mg/kg
LD50 dermal rabbit	> 3000 mg/kg

ethanol, ethyl alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg
LD50 dermal rabbit	> 20000 mg/m³
LC50 inhalation rat (Vapours - mg/l/4h)	124.7 mg/l/4h

acetone, propan-2-one, propanone (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	20000 mg/kg
LC50 inhalation rat (mg/l)	100 mg/l 5h
LC50 inhalation rat (Vapours - mg/l/4h)	76 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
pH: > 2

Serious eye damage/irritation : Causes serious eye irritation.
pH: > 2

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

2-hydroxyethyl methacrylate (868-77-9)	
LC50 fish 1	227 mg/l (96 hours - Pimephales promelas)

ethanol, ethyl alcohol (64-17-5)	
LC50 fish 1	13500 mg/l (96 hours - Pimephales promelas)
EC50 Daphnia 1	54000 mg/l (48 hours - Daphnia magna)
IC50 algae	> 10.9 mg/l (IC50, 72 hours - Skeletonema costatum)

acetone, propan-2-one, propanone (67-64-1)	
LC50 fish 1	635 mg/l (96 hours - Pimephales promelas)

acetone, propan-2-one, propanone (67-64-1)	
EC50 Daphnia 1	10 mg/l (48 hours - Daphnia magna)

12.2. Persistence and degradability

OPTIBOND XTR PRIMER	
Persistence and degradability	No data available.
2-hydroxyethyl methacrylate (868-77-9)	
Biodegradation	84 % (OECD 301D method)
ethanol, ethyl alcohol (64-17-5)	
BOD (% of ThOD)	≥ 0.4 % ThOD BOD5/COD
Biodegradation	85 % (28 days, method: OECD 301D)
acetone, propan-2-one, propanone (67-64-1)	
Persistence and degradability	Biodegradable.
BOD (% of ThOD)	0.96 % ThOD BOD5/COD
Biodegradation	< 78 % (28 days, method: OECD 301B)

12.3. Bioaccumulative potential

OPTIBOND XTR PRIMER	
Bioaccumulative potential	No data.
2-hydroxyethyl methacrylate (868-77-9)	
Bioconcentration factor (BCF REACH)	1,3 - 1,5
Log Pow	0.47
acetone, propan-2-one, propanone (67-64-1)	
Bioconcentration factor (BCF REACH)	0.69
Log Pow	-0.27

12.4. Mobility in soil

OPTIBOND XTR PRIMER	
Ecology - soil	In water, material is partially soluble.

12.5. Results of PBT and vPvB assessment

OPTIBOND XTR PRIMER
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Other adverse effects : None to our knowledge.

Additional information : No other effects known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Regional legislation (waste) : Product is not hazardous waste.

Waste treatment methods : Recover the product with absorbent material. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

European List of Waste (LoW) code : 18 01 06* - chemicals consisting of or containing dangerous substances

SECTION 14: TRANSPORT INFORMATION

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1193

UN-No. (IMDG) : 1193

UN-No. (IATA) : 1193

UN-No. (RID) : 1193

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ETHYL METHYL KETONE (METHYL ETHYL KETONE)

Proper Shipping Name (IMDG) : ETHYL METHYL KETONE (METHYL ETHYL KETONE)

Proper Shipping Name (IATA) : Ethyl methyl ketone

Proper Shipping Name (RID) : ETHYL METHYL KETONE (METHYL ETHYL KETONE)

Transport document description (ADR) : UN 1193 ETHYL METHYL KETONE (METHYL ETHYL KETONE) (acetone, propan-2-one, propanone(67-64-1)), 3, II, (D/E)

Transport document description (IMDG) : UN 1193 ETHYL METHYL KETONE (METHYL ETHYL KETONE), 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3

Danger labels (ADR) : 3

:



IMDG

Transport hazard class(es) (IMDG) : 3

Danger labels (IMDG) : 3

:



IATA

Transport hazard class(es) (IATA) : 3

Hazard labels (IATA) : 3

:



RID

Transport hazard class(es) (RID) : 3

Danger labels (RID) : 3

:



14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1


Limited quantities (ADR) : 1l

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001, IBC02, R001

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions (ADR)	:	TP1
Tank code (ADR)	:	LGBF
Vehicle for tank carriage	:	FL
Transport category (ADR)	:	2
Special provisions for carriage - Operation (ADR)	:	S2, S20
Hazard identification number (Kemler No.)	:	33
Orange plates	:	
Tunnel restriction code (ADR)	:	D/E
EAC code	:	•2YE

- Transport by sea

Limited quantities (IMDG)	:	1 L
Excepted quantities (IMDG)	:	E2
Packing instructions (IMDG)	:	P001
IBC packing instructions (IMDG)	:	IBC02
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP1
EmS-No. (Fire)	:	F-E
EmS-No. (Spillage)	:	S-D
Stowage category (IMDG)	:	B
Flash point (IMDG)	:	-1°C c.c.
Properties and observations (IMDG)	:	Colourless liquid. Flashpoint: -1°C c.c. Explosive limits: 1.8% to 11.5% Miscible with water.

- Air transport

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y341
PCA limited quantity max net quantity (IATA)	:	1L
PCA packing instructions (IATA)	:	353
PCA max net quantity (IATA)	:	5L
CAO packing instructions (IATA)	:	364
CAO max net quantity (IATA)	:	60L
ERG code (IATA)	:	3L

Rail transport

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

National regulations

EC-regulation 453/2010/EC, 1907/2006/EC (REACH), 1272/2008/EC (CLP), 790/2009/EC. Transport of dangerous goods (ADR/RID, IMDG, IATA/ICAO). Workplace exposure limits.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

SECTION 16: OTHER INFORMATION

Indication of changes:

Hazards identification. Regulatory information.

2.1	Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]	Removed	
3.2	Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]	Removed	

Date of issue	:	24/11/2010
Revision date	:	04/09/2015
Supersedes	:	08/08/2014
Signature	:	A. Åsebø Murel

Full text of H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

The information in this safety data sheet is based on information from the manufacturer/supplier, present European and national legislation, and presupposes that the product is used within the specified area of application.